

07-21-00

A

JC490 U.S. PTO

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)

Approved for use through 09/30/2000. OMB 0851-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY
PATENT APPLICATION
TRANSMITTAL

Attorney Docket No. CISCO-1608

First Inventor or Applicant Identifier Brian Lo Bue et al.

Title USB Encapsulation for Network Transmission

Express Mail Label No. EL575422774US

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231JC815 U.S. PTO
09/618950

1. ☐ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification (Total Pages 32)
(preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) (Total Sheets 12)
4. Oath or Declaration (Total Pages 1)
- a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - c. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS/PTO-1449) ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ Small Entity Statement filed in prior application,
Statement(s) ☐ Status still proper and desired
(PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other:

NOTE FOR ITEMS 12-15: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY
FEES, A SMALL ENTITY STATEMENT IS REQUIRED ON C.F.R. § 1.171, EXCEPT
IN ONE CASE: A PRIOR APPLICATIONS RELIED UPON OF C.F.R. § 1.211.


16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
- ☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____

Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Labelor ☐ Correspondence address below

Name	David B. Ritchie				
	D'Alessandro & Ritchie				
Address	P. O. Box 640640				
City	San Jose	State	CA	Zip Code	95164-0640
Country	USA	Telephone	408-441-1100	Fax	408-441-8400

Name (Print/Type)	David B. Ritchie	Registration No. (Attorney/Agent)	31,562
Signature		Date	7-19-00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

07/19/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:) Art Unit:
)
 Brian Lo Bue, et al.) Examiner:
)
 Serial No. [Not yet assigned])
)
 Filed: July 19, 2000)
)
 For: USB ENCAPSULATION FOR)
NETWORK TRANSMISSION)

JC815 U.S. PTO
 09/618950
 07/19/00


CERTIFICATE OF MAILING

"Express Mail" mailing label no: EL575422774US

Date of Deposit: July 19, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to:

Box Patent Application
 Assistant Commissioner for Patents
 Washington, D.C. 20231


 Diane Morse

TRANSMITTAL LETTER

Honorable Assistant Commissioner
 for Patents
 Box Patent Application
 Washington, D.C. 20231

Dear Sir:

Enclosed for filing please find the patent application for an invention entitled,
 "USB ENCAPSULATION FOR NETWORK TRANSMISSION", filed on behalf of
 Cisco Technology, Inc., assignee from inventors Brian Lo Bue, Darrell Shively, Larry

Nadeau and Thomas Roden, including Utility Patent Application Transmittal, 21 pages of specification, 10 pages of claims, 12 sheets of drawing figures, and 1 page of Abstract.

The attorney's Docket Number is CISCO-1608.

Kindly address all communications regarding this application to:


David B. Ritchie
D'Alessandro & Ritchie
P.O. Box 640640
San Jose, CA 95164-0640
Telephone (408) 441-1100

No fee is being paid at this time.

Respectfully submitted,

D'ALESSANDRO & RITCHIE

Dated: July 19, 2000



David B. Ritchie
Reg. No. 31,562

D'Alessandro & Ritchie
P.O. Box 640640
San Jose, CA 95164-0640
(408) 441-1100

This application is submitted in the name of inventors Brian Lo Bue, Darrell Shively, Larry Nadeau and Thomas Roden, all assignors to Cisco Technology, Inc., a California Corporation.

5

SPECIFICATION

TITLE OF INVENTION

USB ENCAPSULATION FOR NETWORK TRANSMISSION

10

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to computer networking. More particularly, the invention relates to networking peripheral universal serial bus (USB) devices.

15

Background Art

A personal computer or workstation tends to have a standard set of input devices to allow it to be controlled. These devices include: keyboard, mouse, joystick, game pad and steering wheel. The Universal Serial bus (USB) is available as a single bus that can accommodate these devices.

20

Computers implement USB as a host. The host is the one master on an instance of USB. All USB devices are slaves. The only device that has any mastering capabilities is a USB hub. USB hubs are allowed to assert master

signaling on their downstream ports only in immediate and direct response to signaling on their upstream port.

A computer accesses a USB device via a Host Controller Driver (HCD).

- 5 The HCD allows the computer to determine what USB devices are attached, characterize them, enable them and use them. For example, a keyboard may be discovered and configured as a system input device.

- 10 Network devices are typically not equipped to be USB hosts. Even if they were, cabling requirements and distance limitations would restrict the usefulness of USB as a network peripheral bus. Network devices are typically controlled either by a local serial port running a simple terminal protocol, or a network protocol (e.g. telnet, SNMP) running over an IP network. The network protocols used to interact with a network device are typically device independent and are
15 used for special purpose status and control functions or network services.

- 20 In some cases, it is desirable that USB peripheral devices be able to interact with network devices. For example, such functionality would allow a USB device to interface with network devices over a network without the need for a standard terminal or computer. Also, this would allow applications such as remote gaming to be enhanced because raw device input data could be routed to a remote server

where the game was running. This would allow users without computers (other than a gateway) to run arbitrarily complex games and applications.

SUMMARY OF THE INVENTION

A universal serial bus (USB) remote host control driver includes a connection to a local network, a network protocol stack and a memory for storing network addresses of USB device adapters and USB devices on the network. A

5 USB device adapter has one or more USB ports, a network connection, a network address, and a network protocol stack. Together, the USB remote host control driver and the USB device adapter enable interaction between a network computer and peripheral USB devices on the network.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing a USB remote host control driver
5 connected over a local network to a USB device via a USB device adapter in
accordance with a specific embodiment of the present invention.

FIG. 2 is a block diagram of a USB device adapter in accordance with a
specific embodiment of the present invention.

FIG. 3 is a block diagram of a USB remote host control driver in
accordance with a specific embodiment of the present invention.

FIG. 4 is a block diagram of a USB remote host control driver in
15 accordance with a specific embodiment of the present invention.

FIG. 5 is a process flow diagram showing a method of providing a signal
from a USB device over a local network to a local processor in accordance with a
specific embodiment of the present invention.

FIG. 6 is a process flow diagram showing a method of establishing a connection between a local processor and a USB device over a local network in accordance with a specific embodiment of the present invention.

5 FIG. 7 is a process flow diagram showing a method of providing a signal from a USB device to a processor on the Internet in accordance with a specific embodiment of the present invention.

10 FIG. 8 is a process flow diagram showing a method of providing the identification of USB device adapters in a network in accordance with a specific embodiment of the present invention.

15 FIG. 9 is a process flow diagram showing a method of providing the identification of USB device adapters in a network in accordance with a specific embodiment of the present invention.

FIG. 10 is a process flow diagram showing a method of providing the identification of USB devices connected to USB device adapters in a network in accordance with a specific embodiment of the present invention.

FIG. 11 is a process flow diagram showing a method of data communication between a local processor and a USB device in accordance with a specific embodiment of the present invention.

5 FIG. 12 is a process flow diagram showing a method of data communication between a local processor and a USB device in accordance with a specific embodiment of the present invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Those of ordinary skill in the art will realize that the following description of the present invention is illustrative only and not in any way limiting. Other embodiments of the invention will readily suggest themselves to such skilled persons having the benefit of this disclosure.

FIG. 1 is a block diagram showing a USB remote host control driver connected over a network to a USB device via a USB device adapter in accordance with a specific embodiment of the present invention. Network 10 includes a computer 12 and a USB device 14. The network 10 may be located in a residence, for example. Instead of connecting the USB device 14 directly to the computer 12, as in the prior art, the USB device 14 is connected to a USB device adapter 18. The computer is connected to, or includes internally, a USB remote host control driver 16. The USB device adapter 18 communicates with the USB remote host control driver 16 via the network. For example, the network may be a local network such as an Ethernet 20 having connections 22, 24 for other computers and/or devices. The invention is also suitable for IP networks such as a WAN or the Internet.

FIG. 2 is a block diagram of a USB device adapter in accordance with a specific embodiment of the present invention. USB device adapter 30 has a connection 32 to a network 34. USB device adapter 30 also has ports 36, 38, 40

for USB devices. For example, USB device 42 is connected to port 36 and USB device 44 is connected to port 38. USB device adapter 30 includes a USB protocol stack 46. The USB protocol stack 46 receives USB packets from, and transmits USB packets to, USB devices 42, 44. USB packets received from the devices are passed to a USB to network bridging task 47. Bridging task 47 garners addressing information and passes the USB packets and the addressing information to a Network Protocol Stack 49. Network Protocol Stack 49 encapsulates USB packets produced by the USB devices into network packets and transmits the network packets onto the network 34. The USB device adapter 30 also receives network packets from the network 34 and decapsulates USB packets from network packets before providing them to the USB devices. The USB device adapter also includes its own address 48 as well as the address 50 of its master USB remote host control driver, allowing identification on the network.

FIG. 3 is a block diagram of a USB remote host control driver in accordance with a specific embodiment of the present invention. In the example shown, the USB remote host control driver 60 is implemented as a component of a computer 62. Though not shown, it is also possible to implement the USB remote host control driver separate but connected to a computer.

The USB remote host control driver 60 communicates with a local network 68 via a connection 66. The USB remote host control driver 60 includes a protocol

stack 70. The protocol stack 70 receives network packets from, and transmits network packets to, the network 68. USB packets decapsulated from network packets are passed to and from a USB and Network bridging task 71, which garners addressing information from the protocol stack 70 and memory, and

5 which, in turn, passes the USB packets to and from a USB host control driver 73. The protocol stack 70 also encapsulates USB packets into network packets and transmits the network packets on the network 68. The USB remote host control driver 60 includes a polling routine 72 for identifying and enabling USB devices onto the network 68. The polling routine 72 uses a candidate list 74 containing

10 possible addresses of USB device adapters 76 to search the network for USB device adapters and USB devices. Once the devices are found, the addresses of networked USB device adapters 80 and USB devices 81 are incorporated into a master list 78. The USB remote host control driver 60 also includes its own network address 82 allowing its identification on the network 68.

FIG. 4 is a block diagram of a USB remote host control driver in accordance with a specific embodiment of the present invention. In this figure, the same USB remote host control driver 60 is shown as in FIG. 3, except that the computer 62 is implemented as a gateway and communications controller. This

20 implementation demonstrates several advantages of the invention. The computer 62 has ports 84, 86, 88, 90, 92 for many utilities and devices including Internet 94, local output to video/TV 96, local (on location) telephone 98, TV cable input 100

and telephone utility 102. It will be appreciated that many other utilities and devices may be connected to the computer 62.

One application of the invention utilizes the Internet 94 and the local TV/video output 96. In this application, a user may interact with an Internet server by a USB device on the local network without the need for any local computer other than the gateway. USB control signals, from a keyboard or joystick for example, are sent over the local network to the computer 62 and routed to the Internet server. Signals from the Internet server may be returned to the user via the local video/TV output. Such an implementation allows users without computers (other than a gateway) to run arbitrarily complex games and applications.

In general, the invention allows USB devices to interface with network devices without the need for a standard terminal or computer. In an example using only the local network, a USB cameras and video outputs could be used to provide two-way communication on a network using only a central computer 62.

FIG. 5 is a process flow diagram showing a method of providing a signal from a USB device over a local network to a local processor in accordance with a specific embodiment of the present invention. In the method, a USB packet is generated at the USB device 110. The, the USB packet is encapsulated in one or more network packets 112 by the USB device adapter. The network packets are

transmitted over the network 114. In the protocol stack of the USB remote host control driver, the USB packet is decapsulated from the network packets 116. Then, the USB packet is provided to the processor 118 for further processing. It will be appreciated that this method is completely reversible. When transmitting

5 control signals or data (e.g., output to USB speakers), the processor-generated USB signals are encapsulated, transmitted over the network, and decapsulated at the destination USB device.

FIG. 6 is a process flow diagram showing a method of establishing a

10 connection between a local processor and a USB device over a local network in accordance with a specific embodiment of the present invention. In this method, a USB device adapter candidate list is configured 130. The list includes the network address of at least one USB device adapter. Configuration may be performed manually, or may be accomplished by a “plug-and-play” routine. The

15 polling routine polls an address on the candidate list 132. This polling includes encapsulating a USB packet in one ore more network packets. If a USB device adapter is present at the address, the polling routine receives a positive response from the USB device adapter 134. The process includes decapsulating a USB packet from one ore more network packets. Once the positive response is

20 recognized, the address and a USB device adapter identifier is added to a master list of USB device adapters on the network 136.

To identify USB devices connected to a USB device adapter on the network, a port on a USB adapter device on the master list is polled by the polling routine 138. Such polling also includes encapsulating a USB packet in one or more network packets. If a USB device is present at the port, a positive response from a USB device connected to said port is received 140. Again, such receiving including decapsulating a USB packet from one or more network packets. Finally, the responding USB device is enumerated in the operating system of the gateway 142.

Both steps 130-136 and steps 138-142 are loops, and each loop may be repeated several times.

FIG. 7 is a process flow diagram showing a method of providing a signal from a USB device to a processor on the Internet in accordance with a specific embodiment of the present invention. In the method, a USB packet is generated at the USB device 150. The USB packet is encapsulated in one or more local network packets 152. The local network packets are transmitted over the local network 154. Upon arriving at the gateway, the USB packet are decapsulated from the local network packets 156. Then, based on previously provided instructions, the USB packet is encapsulated in one or more IP packets 158. The IP packets are transmitted over the Internet 160. Finally, the IP packets are provided to the processor at their destination on the Internet 162.

FIG. 8 is a process flow diagram showing a method of providing the identification of USB device adapters in a network in accordance with a specific embodiment of the present invention. The method is performed by the USB remote host control driver. At the beginning of the method, a candidate list of addresses for possible USB device adapters has already been configured.

The method starts by going to the beginning of the candidate list 170. The routine determines if there is an unpolled address on the candidate list 172. If so, the routine polls the address 174. The routine determines if a USB device adapter responds 176. If a USB device adapter responds to the polling, the USB device adapter is added to the master list 178. The process continues for each address on the candidate list until all the addresses on the candidate list have been polled.

Once the master list is compiled, the routine may determine whether the operating system (OS) of the computer supports automatic insertion of USB devices 180. If the OS supports automatic insertion, it is allowed to do so 182. However, the OS still requires the protocol stack of the USB remote host control driver to communicate with the USB devices through the USB device adapter.

It is also possible to dynamically detect if new device adapters were introduced, enabled, or connected to the system. Such functionality requires that

the candidate list be embedded in the system or be dynamically generated, in addition to regular polling of the network for new devices.

FIG. 9 is a process flow diagram showing a method of providing the identification of USB device adapters in a network in accordance with a specific embodiment of the present invention. If the OS does not support automatic insertion of USB devices, the polling routine must perform this task. The routine starts at the top of the master list 184. For each USB device adapter on the list, the routine polls the ports of the USB device adapter and identifies and enumerates USB devices connected to the USB device adapter 188.

FIG. 10 is a process flow diagram showing a method of providing the identification of USB devices connected to USB device adapters in a network in accordance with a specific embodiment of the present invention. In enumerating USB devices connected to a USB device adapter on the master list, the routine first resets all the ports on the USB device adapter 190. Then, the routine begins at the top of the list of ports 192. For as long as there are ports left on the list 194, the routine determines by polling if there is a device attached to the port 196. If so, the device is assigned an address in the USB remote host control driver 198. The routine then determine if the attached device is a hub or a peripheral device 200. If the attached device is a peripheral, the USB remote host control driver is

configured accordingly. If the device is a hub, the ports on the hub are polled and downstream USB devices are enumerated 202.

FIG. 11 is a process flow diagram showing a method of data

5 communication between a local processor and a USB device in accordance with a specific embodiment of the present invention. Once a USB device is enumerated according to the invention, the processor as a master must enable the device as a slave. To allow communication with a device, the processor allocates a unique transaction identification for the device 210. An encapsulated read/write request is
 10 sent to the device over the network 212. The network packet header of the read/write request will include the processor address, the device address and additional unique information. If the request is acknowledged properly 214 and data is returned 216, the transaction identification is retired 218 and a response may be returned to the device with a new transaction identification 220. If no data
 15 is immediately returned from the device after a proper acknowledgment, the process will sleep and wait for data to be transmitted from the device 222.

FIG. 12 is a process flow diagram showing a method of data

communication between a local processor and a USB device in accordance with a
 20 specific embodiment of the present invention. After a device is enabled by assignment of a unique transaction identification, the processor may receive a packet from the device 230. If the identification of the packet is matched 232, the

transaction identification is retired 234 and the processor responds to the decapsulated data according to the task that spawned the transaction identification 236.

5 In one aspect the invention comprises a universal serial bus (USB) remote host control driver having a connection to a network. The network is further connecting to one or more USB device adapters. Each of said device adapters has a discrete network address. The driver has a network protocol stack. The protocol stack is for encapsulating USB packets in network packets and for decapsulating
10 USB packets from network packets. The driver also has a memory for storing the network address of each of the device adapters and for storing an identification of each USB device connected to each of the device adapters. The driver may further include a polling routine, which contacts each of the device adapters, identifies each of the USB devices, and stores the identifications in the memory. The
15 network packets may be Ethernet packets.

In another aspect, the invention includes a USB device adapter having one or more USB ports, a connection to a network where the network is connected to a USB remote host control driver, a network address, and a network protocol stack
20 where the protocol stack is for encapsulating USB packets in network packets and for decapsulating USB packets from network packets. The network packets may be Ethernet packets.

In another aspect, the invention includes an Internet gateway, comprising a connection to the Internet. The gateway also includes a universal serial bus (USB) remote host control driver having a connection to a local network where the local network further connects to one or more USB device adapters and each of the device adapters has a discrete network address. The driver has a network protocol stack for encapsulating USB packets in network packets and for decapsulating USB packets from network packets. The driver has a memory for storing the network address of each of the device adapters and for storing an identification of each USB device connected to each of the device adapters. The driver also has a polling routine for contacting each of the device adapters, identifying each of the USB devices, and storing the identifications in the memory. The local network may be an Ethernet. The gateway may also include a processor for receiving unencapsulated USB packets from the protocol stack. The gateway may have a connection to a local video monitor, a connection to a local telephone, a connection to a public television cable, and/or a connection to a public telephone network.

In another aspect, the invention includes a method of providing a signal from a USB device over a local network to a local processor. The method comprises generating a USB packet at the USB device, encapsulating the USB packet in one or more network packets, transmitting the network packets over the

network, decapsulating the USB packet from the network packets, and providing the USB packet to the processor. Again, the local network may be an Ethernet. The USB device may be a keyboard.

5 In another aspect, the invention includes a method of establishing a connection between a local processor and a USB device over a local network. The method comprises configuring a USB device adapter candidate list where the list includes the network address of at least one USB device adapter, polling an address on the candidate list where the polling includes encapsulating a USB
10 packet in one ore more network packets, receiving a positive response from a USB device adapter to said polling where the receiving includes decapsulating a USB packet from one ore more network packets, and adding the address and a USB device adapter identifier to a master list. The method may further comprise polling a port on a USB adapter device on the master list where the polling includes
15 encapsulating a USB packet in one ore more network packets, receiving a positive response from a USB device connected to said port where the receiving includes decapsulating a USB packet from one ore more network packets, and enumerating a USB device in the operating system of the processor.

20 In yet another aspect, the invention includes a method of providing a signal from a USB device to a processor on the Internet. The method comprises generating a USB packet at the USB device, encapsulating the USB packet in one

or more local network packets, transmitting the local network packets over a local network, decapsulating the USB packet from the local network packets, encapsulating the USB packet in one or more IP packets, transmitting the IP packets over the Internet, and providing the IP packets to the processor.

5

It will be appreciated that either or both of the USB device adapter or the USB remote host control driver may be implemented in hardware, or software stored on a computer-readable medium, or a combination of hardware and software.

10

The method is compatible with many types of local network protocols including Ethernet, ATM and IP. For the purposes of this application, Ethernet and ATM frames are herein referred to as packets. Ethernet is a presently preferred implementation of this invention due to its widespread use in local networks.

15

All types of USB devices are compatible with this invention, including, but not limited to, keyboards, mice, joysticks, cameras, speakers and touch pads.

20

While embodiments and applications of this invention have been shown and described, it would be apparent to those skilled in the art having the benefit of this disclosure that many more modifications than mentioned above are possible

without departing from the inventive concepts herein. The invention, therefore, is not to be restricted except in the spirit of the appended claims.

What is claimed is:

1. A universal serial bus (USB) remote host control driver, comprising:

5 a connection to a network, said network further connecting to one or more USB device adapters, each of said device adapters having a discrete network address;

a network protocol stack, said protocol stack for encapsulating USB packets in network packets and for decapsulating USB packets from network
10 packets; and

a memory for storing the network address of each of said device adapters and for storing an identification of each USB device connected to each of said device adapters.

15 2. The USB remote host control driver of claim 1, further comprising:

a polling routine, said polling routine contacting each of said device adapters, identifying each of said USB devices, and storing the identifications in said memory.

20 3. The USB host control driver of claim 1, where the network packets are Ethernet packets.

4. A USB device adapter comprising:

one or more USB ports;

a connection to a network, said network connected to a USB remote host control driver;

5 a network address;

a network protocol stack, said protocol stack for encapsulating USB packets in network packets and for decapsulating USB packets from network packets.

10 5. The USB host control driver of claim 4, where the network packets are Ethernet packets.

6. An Internet gateway, comprising:

a connection to the Internet; and

15 a universal serial bus (USB) remote host control driver, said USB remote host control driver having:

(a) a connection to a local network, said local network further connecting to one or more USB device adapters, each of said device adapters having a discrete network address;

20 (b) a local network protocol stack, said protocol stack for encapsulating USB packets in local network packets and for decapsulating USB packets from local network packets;

(c) a memory for storing the network address of each of said device adapters and for storing an identification of each USB device connected to each of said device adapters; and

(d) a polling routine, said polling routine contacting each of said
5 device adapters, identifying each of said USB devices, and storing the identifications in said memory.

7. The Internet gateway of claim 6, where the local network is an Ethernet.

10 8. The Internet gateway of claim 6, further comprising:
a processor, said processor for receiving unencapsulated USB packets from the protocol stack.

15 9. The Internet gateway of claim 8, further comprising:
a connection to a local video monitor.

10. The Internet gateway of claim 8, further comprising:
a connection to a local telephone.

20 11. The Internet gateway of claim 8, further comprising:
a connection to a public television cable.

12. The Internet gateway of claim 8, further comprising:

a connection to a public telephone network.

13. A method for providing a signal from a USB device over a local network to

5 a local processor, the method comprising:

generating a USB packet at the USB device;

encapsulating the USB packet in one or more network packets;

transmitting the network packets over the network;

decapsulating the USB packet from the network packets; and

10 providing the USB packet to the processor.

14. The method of claim 13, wherein the local network is an Ethernet.

15. The method of claim 13, wherein the USB device is a keyboard.

16. A method for establishing a connection between a local processor and a
USB device over a local network, the method comprising:

configuring a USB device adapter candidate list, said list including the
network address of at least one USB device adapter;

20 polling an address on the candidate list, said polling including encapsulating
a USB packet in one or more network packets;

receiving a positive response from a USB device adapter to said polling,
 said receiving including decapsulating a USB packet from one or more network
 packets; and

adding the address and a USB device adapter identifier to a master list.

5

17. The method of claim 16, further comprising:

polling a port on a USB adapter device on the master list, said polling
 including encapsulating a USB packet in one or more network packets;

receiving a positive response from a USB device connected to said port,
 10 said receiving including decapsulating a USB packet from one or more network
 packets; and

enumerating a USB device in the operating system of the processor.

18. A method for providing a signal from a USB device to a processor on the

15 Internet, the method comprising:

generating a USB packet at the USB device;

encapsulating the USB packet in one or more local network packets;

transmitting the local network packets over a local network;

decapsulating the USB packet from the local network packets;

20 encapsulating the USB packet in one or more IP packets;

transmitting the IP packets over the Internet; and

providing the IP packets to the processor.

19. An apparatus for providing a signal from a USB device over a local network to a local processor, comprising:

means for generating a USB packet at the USB device;

means for encapsulating the USB packet in one or more network packets;

5 means for transmitting the network packets over the network;

means for decapsulating the USB packet from the network packets; and

means for providing the USB packet to the processor.

20. The apparatus of claim 19, wherein the local network is an Ethernet.

21. The apparatus of claim 19, wherein the USB device is a keyboard.

22. An apparatus for establishing a connection between a local processor and a USB device over a local network, comprising:

15 means for configuring a USB device adapter candidate list, said list including the network address of at least one USB device adapter;

means for polling an address on the candidate list, said means for polling including means for encapsulating a USB packet in one or more network packets;

means for receiving a positive response from a USB device adapter to said
20 polling, said means for receiving including means for decapsulating a USB packet from one or more network packets; and

means for adding the address and a USB device adapter identifier to a master list.

23. The apparatus of claim 22, further comprising:

5 means for polling a port on a USB adapter device on the master list, said means for polling including means for encapsulating a USB packet in one or more network packets;

means for receiving a positive response from a USB device connected to said port, said means for receiving including means for decapsulating a USB packet from one or more network packets; and

10 means for enumerating a USB device in the operating system of the processor.

24. An apparatus for providing a signal from a USB device to a processor on the Internet, comprising:

means for generating a USB packet at the USB device;

means for encapsulating the USB packet in one or more local network packets;

means for transmitting the local network packets over a local network;

20 means for decapsulating the USB packet from the local network packets;

means for encapsulating the USB packet in one or more IP packets;

means for transmitting the IP packets over the Internet; and

means for providing the IP packets to the processor.

25. A program storage device readable by a machine, embodying a program of
5 instructions executable by the machine to perform a method for providing a signal
from a USB device over a local network to a local processor, the method
comprising:

generating a USB packet at the USB device;

encapsulating the USB packet in one or more network packets;

10 transmitting the network packets over the network;

decapsulating the USB packet from the network packets; and

providing the USB packet to the processor.

26. The device of claim 25, wherein the local network is an Ethernet.

27. The device of claim 25, wherein the USB device is a keyboard.

28. A program storage device readable by a machine, embodying a program of
instructions executable by the machine to perform a method for establishing a
20 connection between a local processor and a USB device over a local network, the
method comprising:

configuring a USB device adapter candidate list, said list including the network address of at least one USB device adapter;

polling an address on the candidate list, said polling including encapsulating a USB packet in one or more network packets;

5 receiving a positive response from a USB device adapter to said polling, said receiving including decapsulating a USB packet from one or more network packets; and

adding the address and a USB device adapter identifier to a master list.

10 29. The device of claim 28, wherein the method further comprising:

polling a port on a USB adapter device on the master list, said polling including encapsulating a USB packet in one or more network packets;

receiving a positive response from a USB device connected to said port, said receiving including decapsulating a USB packet from one or more network
15 packets; and

enumerating a USB device in the operating system of the processor.

30. A program storage device readable by a machine, embodying a program of instructions executable by the machine to perform a method for providing a signal

20 from a USB device to a processor on the Internet, the method comprising:

generating a USB packet at the USB device;

encapsulating the USB packet in one or more local network packets;

transmitting the local network packets over a local network;
decapsulating the USB packet from the local network packets;
encapsulating the USB packet in one or more IP packets;
transmitting the IP packets over the Internet; and
5 providing the IP packets to the processor.

ABSTRACT OF THE DISCLOSURE

A universal serial bus (USB) remote host control driver includes a connection to a local network, a network protocol stack and a memory for storing network addresses of USB device adapters and USB devices on the network. A USB device adapter has one or more USB ports, a network connection, a network address, and a network protocol stack. Together, the USB remote host control driver and the USB device adapter enable interaction between a network computer and peripheral USB devices on the network.

10

15

CISCO-1608




FIG. 1

10

CISCO-1608




FIG. 2

CISCO-1608




FIG. 3




FIG. 4

CISCO-1608




FIG. 5

CISCO-1608




FIG. 6

CISCO - 1608





FIG. 7

CISCO - 1608

FIG. 8

CISCO-1608




FIG. 9

CISCO-1608





FIG. 10

FIG. 11

CISCO-1608




FIG. 12